

METEOR EXTRA SOLV



LIQUID WAX WITH SOLVENT FOR PARQUET AND TERRACOTTA FLOORS

- Easy maintenance and polishing
- Resistant to pedestrian traffic and waterproof
- Semi-gloss finish

Contains a combination of quality waxes for quick, effective protection and maintenance of parquet and terracotta floors, creating a warm polish and maintaining the floor's original colour. Recommended for parquet flooring of great aesthetic quality, to underline the natural look of the wood. Suitable for spraying or applicator use. Polish may be topped up with a single-brush brushing machine at low speed.

HOW TO USE

Allow floor to dry thoroughly, then apply product directly to terracotta or parquet floor, either new or after stripping wax. METEOR EXTRA SOLV can be applied with a brush, applicator or spray can, polishing it instantly with a single-brush brushing machine with a red or white disc. On terracotta floors, it is best to apply 2 coats after waterproofing the surface with IF 11. The product can be used on all surfaces after treatment with IF 110, natural unpolished stone and cement. Repeat treatment 1 to 3 times, until the desired degree of polish is achieved. Do not apply METEOR EXTRA SOLV to hot surfaces or surfaces which have been in the sun, to prevent excessively rapid drying.



DILUTION

Ready to use.

METEOR EXTRA SOLV

 TECHNICAL DATA**ASPECT:** Opaque liquid**COLOR:** Yellow**PERFUME:** Honey**COV:** 90,44%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
		0.785			9,6 ± 1,0

 WARNINGS

Flammable liquid and vapour. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. In case of fire, use a dry powder fire extinguisher to extinguish. Store in a well-ventilated place. Keep cool. Contents HYDROCARBONS, C9-11, ALKANES.



WARNING



WARNING



DANGER

 NOTES

Protect from frost. Shake can before using. If you apply excess product, simply pass a white disc over it to absorb it and even out the surface treatment.

Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

 PACKAGING

Code	Size	Quantity	Pallet
5579	L 5	4	8x4=32