

# **CRIS**



## ANTI-SLIP CRYSTALLISER FOR TREATMENT OF MARBLE, MARBLE COMPOSITION AND TERRAZZO FLOORS

- Anti-slip effect tested by UL laboratories
- Eliminates porosity of calcareous floors
- Glossy effect



Crystalliser for calcareous floors. Eliminates micro-porosity by preventing dirt from penetrating. Excellent glossy effect. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance product.

#### ? HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, when the floor is completely dry, spray a small amount of the product (8-10 ml. per m2) directly onto the floor and use the single disc machine at a low speed (150/170 rpm minimum weight 45 kg) with steel wool pad (grade 00) until completely dry and polished (8-10 min per m2). Repeat if necessary. After treatment, damp mop with a disposal cloth.



#### **DILUTION**

Ready to use.

#### A TECHNICAL DATA

**ASPECT:** Opaque liquid

COLOR: Pink
PERFUME: Floral
COV: 5,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
1,5 ± 0,5	30 ± 2	1.14			



#### **CRIS**

#### (!) WARNINGS

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects. Wear eye protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Contents MAGNESIUMHEXAFLUOROSILICATE.





WARNING

# NOTES

Do not use CRIS at temperatures below 10° C. Keep away from freezing. Sutter Professional cannot be considered liable for any damage due to improper product use.

Only for professional use. Safety data sheet available on request.

### **PACKAGING**

 Code	Size	Quantity	Pallet
5427	Kg 5	4	9x4=36

